

### 1. Identification of Substance:

Product Name: GreenSil FG Company Details:
Green Shield Products

Address:

Product Use: Silicone Coating 40 Cypress Creek Parkway #338

Houston, Texas 77090

Field of Application: building and metal industry

Identified uses: Industrial/Professional use

2

**Telephone:** (844) 922-2355

24 Hr Emorgan

24-Hr. Emergency Phone Number:

Reversible adverse effects in dermal tissue, Draize score: >=

CHEMTREC (800) 424-9300

## 2. Hazards Identification

#### **GHS Ratings:**

Skin corrosive

|                    | _  |  |
|--------------------|----|--|
|                    |    | 2.3 < 4.0 or persistent inflammation                     |
| Eye corrosive      | 2A | Eye irritant: Subcategory 2A, Reversible in 21 days      |
| Skin sensitizer    | 1  | Skin sensitizer  |
| Carcinogen         | 2  | Limited evidence of human or animal carcinogenicity      |
| Reproductive toxin | 2  | Human or animal evidence possibly with other information |

Reproductive toxin 2 Human or animal evidence possibly with other information

Organ toxin single 3 Transient target organ effects- Narcotic effects- Respiratory tract irritation

exposure

H315

Aquatic toxicity C3 Acute toxicity > 10.0 but <= 100.0 mg/l and lack of rapid degradability

and log Kow >= 4 unless BCF < 500 and unless chronic toxicity > 1 mg/l

#### **GHS Hazards**

| 11010 | Causes skill illiation              |
|-------|-------------------------------------|
| H317  | May cause an allergic skin reaction |
| H319  | Causes serious eye irritation       |
| H335  | May cause respiratory irritation    |
| H336  | May cause drowsiness or dizziness   |
| H351  | Suspected of causing cancer         |
|       |                                     |

Causes skin irritation

H361 Suspected of damaging fertility or the unborn child H412 Harmful to aquatic life with long lasting effects

#### **GHS Precautions:**

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash hands thoroughly after handling

P271 Use only outdoors or in a well-ventilated area

P272 Contaminated work clothing should not be allowed out of the workplace

P273 Avoid release to the environment









P280 Wear protective gloves/protective clothing/eye protection/face protection

P281 Use personal protective equipment as required

P312 Call a POISON CENTER or doctor/physician if you feel unwell Specific treatment is urgent (see Section 4 First Aid measures)

P362 Take off contaminated clothing and wash before reuse

P363 Wash contaminated clothing before reuse P302+P352 IF ON SKIN: Wash with soap and water

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses

if present and easy to do - continue rinsing

P308+P313 IF exposed or concerned: Get medical advice/attention P332+P313 If skin irritation occurs: Get medical advice/attention

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P337+P313 Get medical advice/attention

P370+P378 In case of fire: See Section 5 for extinguishing measures

P405 Store locked up

P403+P235 Store in a well ventilated place. Keep cool

P501 Dispose of contents/container in accordance with existing federal, state, and local

environmental control laws.

#### Signal Word: Danger



**Acute** Toxicity:

Eyes: May cause irritation & burns.

Skin: Minor potential for irritation.

Inhalation: Liquid may cause irritation.

Ingestion: May cause irritation & burns.

Conditions Aggravated: Unknown

Chronic Effects: Possible harmful target organ effects.

#### 3. Composition/information on ingredients:

| Chemical Name   | CAS number | Weight Concentration % |  |
|---|------------|------------------------|--|
| Siloxanes and silicones, dimethyl, hydroxy-terminated | 70131-67-8 | 30.00% - 40.00%        |  |
| Quartz  | 14808-60-7 | 30.00% - 40.00%        |  |
| Petroleum distillates, hydrotreated light             | 64742-47-8 | 10.00% - 20.00%        |  |
| Titanium dioxide                                      | 13463-67-7 | 5.00% - 10.00%         |  |
| 2-Butanone, O,O',O"-(methylsilylidyne)                | 22984-54-9 | 1.00% - 5.00%          |  |









| Chemical Name                              | CAS number             | Weight Concentration % |  |
|--|------------------------|------------------------|--|
| Octamethylcyclotetrasiloxane               | 556-67-2 1.00% - 5.00% |                        |  |
| Silica, amorphous, fumed, crystalline-free | 112945-52-5            | 0.10% - 1.00%          |  |
| Ethylbenzene                               | 100-41-4               | 0.00% - 0.10%          |  |
| Naphthalene                                | 91-20-3                | 0.00% - 0.10%          |  |
| Toluene                                    | 108-88-3               | 0.00% - 0.10%          |  |

#### 4. First Aid Measures:

**After Inhalation:** Inhalation: If symptoms ensue, move to fresh air. If breathing is difficult, give oxygen.

After Eye Contact: Rinse opened eye for at least 15 minutes under running water.

Remove contact lenses if present and easy to do so, and continue rinsing. **After Skin Contact:** Clean affected area with soap and plenty of water.

**After Swallowing:** Consult physician. **Notes to Physician:** Treat symptomatically

# 5. Firefighting measures

Flash Point: >200°F, 93°C

LEL: N/A UEL: N/A

Upper and Lower explosive limits listed if known.

Suitable Extinguishing Agents: Water spray, CO2, Foam, Dry chemical

Information about Protection against Explosions and Fires: Closed containers may

rupture when exposed to extreme heat.

Dangerous Products of Decomposition: Oxides of carbon, oxides of nitrogen, oxides of silicon.

**Protective Equipment:** Firefighters should wear a pressure demand self-contained breathing apparatus and protective clothing.

#### 6. Accidental release measures

**Person-Related Safety Precautions:** Evacuate all non-essential personnel. Remove all sources of ignition. **Measures for Environmental Protection:** Cover and contain spill with absorbent material. Collect for proper disposal according to local, state, and federal regulations.

**Small Spills:** Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece) Clean surface thoroughly to remove residual contamination.

**Large Spills:** Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place Into a container for later disposal. Following product recovery, flush area wilh water.









## 7. Handling and Storage

**Information for Safe Handling:** Avoid contact with skin or inhalation.

Storage Requirements: Store in dry, well ventilated area. Avoid contact with moisture.

Keep containers tightly closed. Store between 60°F-100°F. Material may settle.

**Regulatory Requirements:** Store according to all local, state, and federal regulations.

# 8. Exposure Controls and Personal Protection:

| Chemical Name / CAS No.  | OSHA Exposure Limits   | ACGIH Exposure Limits | Other Exposure Limits |
|--|--|-----------------------|-----------------------|
| Siloxanes and silicones, dimethyl, hydroxy-terminated 70131-67-8 | Not Established  | Not Established       | Not Established       |
| Limestone<br>1317-65-3   | 15 mg/m3 TWA (total dust);<br>5 mg/m3 TWA (respirable<br>fraction) | Not Established       | Not Established       |
| Poly(dimethylsiloxane)<br>63148-62-9                             | Not Established  | Not Established       | Not Established       |
| Titanium dioxide<br>13463-67-7                                   | 15 mg/m3 TWA (total dust)  | 10 mg/m3 TWA          | Not Established       |
| 2-Butanone, O,O',O"-(meth-ylsilylidyne)trioxime                  | Not Established  | Not Established       | Not Established       |
| Octamethylcyclotetrasilox-<br>ane<br>556-67-2                    | Not Established  | Not Established       | Not Established       |
| Silica, amorphous, fumed,<br>crystalline-free<br>112945-52-5     | Not Established  | Not Established       | Not Established       |

#### **Engineering Controls**

Use local exhaust ventilation to maintain airborne concentrations below the TLV, especially if heating or spraying. Use only in a well ventilated area to keep vapors below exposure limits. Use local exhaust ventilation if necessary.

**General Protective and Hygienic Measures:** Usual precautionary measures should be adhered to when handling chemicals.

#### **Personal Protective Equipment:**

Respiratory Protection: Do not inhale vapors. Use NIOSH approved respiratory protection if TLV/PEL is ex-

ceeded. Do not enter storage area unless adequately ventilated. **Hand Protection:** Protective butyl rubber or nitrile rubber gloves.

Eye Protection: Chemical safety goggles.

**Body Protection:** Impervious protective work clothing. Launder separately.







# SAFETY DATA SHEET

# **Safety Data**



**Contaminated Gear:** Observe local requirements. Dispose of in accordance with local/state/federal regulations.

# 9. Physical and Chemical Properties:

Physical properties listed where known.

Appearance: White liquid
Vapor Pressure: N/A
Vapor Density: N/A
Specific Gravity: 1.20
Freezing point: N/A
Boiling range: 2500 - 3000°C
Evaporation rate: N/A
Explosive Limits: 1% - 6%

Autoignition temperature: N/A

Odor: Solvent odor Odor threshold: N/A pH: N/A Melting point: N/A Solubility: N/A

Flash point: >200°F,93°CFlammability: N/A

Partition coefficient N/A (n-octanol/water):

Decomposition temperature: N/A

## 10. Stability and Reactivity:

**Incompatible Materials:** Avoid contact with moisture, strong acids, strong bases, oxidizing and reducing agents

Hazardous Polymerization: Not expected to occur.

Dangerous Products of Decomposition: Oxides of carbon, oxides of silicon, and oxides of nitrogen.

# 11. Toxicological Information:

**Mixture Toxicity** 

Inhalation Toxicity LC50: 720mg/L

**Component Toxicity** 

556-67-2 Octamethylcyclotetrasiloxane

Oral LD50: 1,540 mg/kg (Rat) Dermal LD50: 759 mg/kg (Rabbit)

Inhalation LC50: 36 g/m3 (Rat)

**Toxicity Values Listed if Known** 

**Acute Toxicity:** 

Eyes: May cause irritation & burns.

Skin: Minor potential for irritation.

Inhalation: Liquid may cause irritation.

Ingestion: May cause irritation & burns.

Chronic Effects: Possible harmful target organ effects.









**Routes of Entry:** Ingestion, inhalation, skin contact, eye contact **Target Organs:** Eyes, skin, respiratory system, reproductive system.

## **Chemicals with Known or Possible Carcinogenic Effects:**

CAS Number 1317-65-3 13463-67-7 <u>Description</u> Limestone Titanium dioxide % Weight 20 to 30% 5 to 10% Carcinogen Rating Limestone:

Titanium dioxide: NIOSH: potential occupational carcinogen

IARC: Possible human carcinogen

OSHA: listed

## 12. Ecological Information:

**General Information:** Based on experience, no adverse effects are to be expected if correct disposal procedures have been followed as indicated in section 13.

Individual component ecotoxicity listed if known.

**Component Ecotoxicity** 

Octamethylcyclotetrasiloxane 96 Hr LC50 Brachydanio rerio: >500 mg/L; 96 Hr LC50 Lepomis macrochirus:

>1000 mg/L

**Recommendation:** Observe local requirements. Dispose of in accordance with local/state/federal regulations.

**Empty Container Precautions:** Recondition or dispose of empty container in accordance with governmental regulations. If container is to be disposed, ensure all product residues are removed and container is empty prior to disposal.

## 14. Transport Information

#### **DOT Regulated Components:**

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods unless specifically cited below:

<u>Agency Proper Shipping Name UN Number Packing Group Hazard Class None</u>







greenshieldproducts.com



# 15. Regulatory Information:

**OSHA HAZARD COMMUNICATION STANDARD:** This material is classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

SARA 311/312 Hazard Categories: Acute health hazard, chronic health hazard, fire hazard.

## **California Proposition 65**

# (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute unless otherwise listed:

**WARNING:** This product can expose you to chemicals listed below, which are known to the State of California to cause cancer, birth defects, or reproductive harm. For more information, visit www.P65Warnings.ca.gov

Titanium dioxide 13463-67-7 5 to 10 % CARC

Titanium dioxide and Quartz only require Proposition 65 notification when in dust form and particles of respirable size

#### **Massachusetts Right To Know List:**

Titanium dioxide 13463-67-7 5 to 10 % Limestone 1317-65-3 20 to 30 %

#### **New Jersey Right To Know List:**

Titanium dioxide 13463-67-7 5 to 10 % Limestone 1317-65-3 20 to 30 %

#### Pennsylvania Right To Know List:

Titanium dioxide 13463-67-7 5 to 10 % Limestone 1317-65-3 20 to 30 %

#### SARA 302 Extremely Hazardous Substances:

- None

#### Chemicals subject to SARA 313 Reporting:

- None

CountryRegulationAll Components ListedCanadaCanada DSLYesUSToxic Substances Control ActYes







# **16. Other Information:**

Safety Data Sheet issued by Product Safety Department

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Green Shield Products. The data on these sheets relates only to the specific material designated herein. Green Shield Products assumes no legal responsibility for use or reliance upon this data. It is the user's responsibility to ensure that their activities comply with federal, state, or local laws

Date revised: 2022-04-06

Date Prepared: 04/06/2022

Reviewer Revision 1





