



**Spray Polyurethane Foam (SPF)**

**Product**

GreenSeal 2.5	2.5 lbs. PCF Density, Nominal 40 PSI Compressive Strength, UL Listings
GreenSeal 2.8	2.8 lbs. PCF Density, Nominal 60 PSI Compressive Strength, UL Listings, FM Listings, UL EX Evaluation Report
GreenSeal 3.0	3.0 lbs. PCF Density, Nominal 70 PSI Compressive Strength, UL Listings, FM Listings, UL EX Evaluation Report
GreenSeal 3.5	3.5 lbs. PCF Density, Nominal 80 PSI Compressive Strength, UL Listings
GreenSeal 2.5 HFO	2.5 lbs. PCF Density, Nominal 40 PSI Compressive Strength, UL Listings, Higher R-Value, Higher Yield
GreenSeal 2.8 HFO	2.8 lbs. PCF Density, Nominal 60 PSI Compressive Strength, UL Listings, Higher R-Value, Higher Yield
GreenSeal 3.0 HFO	3.0 lbs. PCF Density, Nominal 70 PSI Compressive Strength, UL Listings, Higher R-Value, Higher Yield

Available in reactivities of slow (S), regular (R), and fast (F).

**Silicone Coating**

**Product**

GreenSil 70	69% Solids by Volume, UL Listed, FM, CRRC, NSF, Meets ASTM D6694
GreenSil 100	96% Solids by Volume, UL Listed, FM, Low VOC Compliant (California), CRRC, NSF, Meets ASTM D6694

**Acrylic Coating**

**Product**

GreenCoat	100% Acrylic, 55% solids by volume, White, Tan, Light Gray Colors, UL Listed, CRRC, Meets ASTM D6083
GreenCoat FS	100% Acrylic, Fast Setting, 55% solids by volume, White, Tan, Light Gray Colors, UL Listed, CRRC, Meets ASTM D6083
GreenCoat HT	100% Acrylic, Premium High Tensile, 55% Solids by Volume, White, Tan, Light Gray, UL Listed, CRRC, Meets ASTM D6083
GreenCoat HT FS	100% Acrylic, Premium High Tensile, Fast Setting, 55% Solids by Volume, White, Tan, Light Gray, UL Listed, CRRC, Meets ASTM D6083
GreenCoat OnePass	100% Acrylic, High Build, Fast Setting, 55% solids by volume, White, Tan, Light Gray Colors, CRRC, Meets ASTM D6083
GreenCoat OnePass HT	100% Acrylic, High Build, Fast Setting, Premium High Tensile, 55% solids by volume, White, Tan, Light Gray Colors, CRRC, Meets ASTM D6083

**Polyurethane Coatings**

**New Product**

GreenThane AL	77% Solids by Volume Aliphatic Polyurethane Low VOC Compliant (California)
GreenThane AR	77% Solids by Volume Aromatic Polyurethane Low VOC Compliant (California)



## Other Coatings

### Product

GreenTuff	100% Solids, Two Component, Fast Cure Polyurea, High Impact Resistance,
GreenTuff CR	100% Solids, Two Component, Fast Cure Polyurea, High Impact Resistance, Chemical Resistance

## Primers

### Product

GreenPrime Epoxy	Two Component Epoxy For Existing Roof Substrates, Roof Restoration Or SPF Application, FM Listed
GreenPrime GP	Black Acrylic Single Component For Existing Roof Substrates, Roof Restoration Or SPF Application
GreenPrime BB	Red Single Component Water Based Primer For Existing Asphalt Roof Substrates To Block Bleed Through
GreenClean	Single Component Wash Primer For Existing Single-Ply Roof Substrates, Roof Restoration Or SPF Application
GreenPrime SP	Ivory Or Black Acrylic Single Component For Existing Single-Ply Roof Substrates, Roof Restoration
GreenPrime Metal	Dark Red Acrylic Single Component Rust Inhibitive Primer For Existing Metal Roof Substrates, Roof Restoration Or SPF Application. Low VOC, Solvent Based Primer, Optimal Adhesion to New or Existing TPO
GreenPrime TPO	Low VOC, Solvent Based Primer, Optimal Adhesion to New or Existing TPO

## Accessories and Sealants

### Product

GreenCoat FG	Single Component Acrylic Mastic
GreenSII FG	Single Component, 100% Silicone Mastic
GreenFibers	Fiber Additive to GSP Coatings to Thicken, Reinforce, and Create Sealing and Patching Material
GreenFabric	Rolls of Fabric in 4, 6, 12 and 40 Inch Wide for Embedment into Coating Systems for Reinforcement